

□ **General Purpose Container 20**

- Suitable for any general cargo.
- Containers may be equipped with liner bags suitable for bulk cargo, e.g. malt.
- Fork-lift pockets on a number of containers.
- Various lashing devices on the top and bottom longitudinal rails and the corner posts.
- Lashing devices have a permissible load of 1,000kg (2,205lbs) each.
- Note permissible weight limits for road and rail transport.



Construction	Inside Dimensions			Door Opening		Weights			Capacity	
	Length	Width	Height	Width	Height	Max. Gross	Tare	Max. Payload		
	mm ft	mm ft	mm ft	mm ft	mm ft	kg lbs	kg lbs	kg lbs		
<b>8'6" high</b>										
Steel with walk floor	container corrugated and wooden	5895 19'4"	2350 7'8 1/2"	2392 7'10"	2340 7'8"	2292 7'6 1/4"	30400 67200	2250 4950	28100 62140	33.2 1172
		5895 19'4"	2350 7'8 1/2"	2392 7'9"	2340 7'8"	2292 7'6 1/4"	28000 62010	2250 4950	25750 57060	33.2 1172
		5879 19'3"	2330 7'7"	2370						

**General Purpose Container 40**

- Suitable for any general cargo.
- Various lashing devices on the top and bottom longitudinal rails and the corner posts.
- Lashing devices have a permissible load of 1,000 kg (2,205 lbs) each.
- Note permissible weight limits for road and rail transport.



# Ocean Containers Specifications

Construction	Inside Dimensions			Door Opening		Weights			Capacity
	length	width	height	width	height	Max. Gross	Tare	Max. Payload	
	mm #	mm #	mm #	mm #	mm #	kg lbs	kg lbs	kg lbs	
8'6" high									
Steel container with corrugated walls and wooden floor	20299 66.6	2340 7.68	2395 7.86	2340 7.68	2292 7.53	3040 6700	4740 10450	5670 12480	67.7 2390

For the full range of specifications, visit our website at [www.ups.com](http://www.ups.com). This information is for informational purposes only. It is not intended to be used as a sales or marketing tool. The information is subject to change without notice. © 2010 UPS of America, Inc. All rights reserved.



Construction	Inside Dimensions				Weights			Capacity
	length	width	height	height	Max. Gross	Tare	Max. Payload	
	mm #	mm #	middle mm #	side mm #	kg lbs	kg lbs	kg lbs	
8'6" high								
Steel container with corrugated walls, wooden floor and removable tarpaulin	5888 19.312	2345 7.8	2365 7.9	2315 7.7	3040 6700	2250 4960	2830 6240	33.2 11.90
	5887 19.4	2360 7.89	2377 7.95	2347 7.5	3040 6700	2350 5180	2810 6200	32.6 11.66

Options for the full range of specifications, visit our website at [www.ups.com](http://www.ups.com). This information is for informational purposes only. It is not intended to be used as a sales or marketing tool. The information is subject to change without notice. © 2010 UPS of America, Inc. All rights reserved.

Construction	Inside Dimensions				Weights			Capacity
	length	width	height	height	Max. Gross	Tare	Max. Payload	
	mm #	mm #	middle mm #	side mm #	kg lbs	kg lbs	kg lbs	
8'6" high								
Steel container with corrugated walls, wooden floor and removable tarpaulin	12059 39.50	2342 7.9	2376 7.95	2326 7.79	3040 6700	3810 8400	2670 5890	65.6 2310
	12022 39.50	2345 7.8	2365 7.9	2315 7.7	3040 6700	3740 8255	2610 5795	65.3 2306
	12030 39.5	2340 7.89	2377 7.95	2347 7.7	3040 6700	3850 8490	2640 5870	65.4 2345